

# Professional Online Academy Vu Topper RM



## IT601-P System and Network Practical Update MCQ'S Final Term



Follow Us on YouTube:  
[@vutopperrm](https://www.youtube.com/@vutopperrm)

For More Help Contact What's app Me!!!  
Number's = # 0322-4021365, 0316-4980094

[Rizwan Manzoor](https://www.youtube.com/@vutopperrm)  
[Vu Topper RM](https://www.youtube.com/@vutopperrm)

وَتَعَزُّ مَنْ تَشَاءُ وَتَذِلُّ مَنْ تَشَاءُ



### *Our Services*

- Assignments
- Quiz & Gdb's
- LMS Handling
- Online Classes
- Lectures Views
- Project Handling
- Important Notes

**Result**

**85% To 100%**

پہلے ہمارے سٹوڈنٹس کے رزلٹ دیکھیں  
پھر ہم سے سروسز لیں



[www.youtube.com/@vutopperrm](https://www.youtube.com/@vutopperrm)



**Contact us**

**0322 4021365**

**0316 4980094**

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

For More Help Contact What's app 03224021365

**Question No:1**

**(Marks:1)**

**Vu-Topper RM**

Consider the following command and select the true statement about it.

`ldapsearch -x -LLL -b dc=vusna, dc=com '(uid=arif)' cn gidNumber`

A. Command is incorrect, all switches should be specified with -- instead of -

**B. Command is correct and it will display DN**

C. Command is incorrect, '(uid=arif)' should be replaced with , uid=arif

D. Command is incorrect, -LLL should be -L

**Question No:2**

**(Marks:1)**

**Vu-Topper RM**

Consider the following command and select the correct statement about it.

`mount -t nfs 192.168.19.6:/nfs_shares/public /var/nfs/nfs_home`

A. After execution of the command, /var/nfs/nfs\_home will NOT be synced with /nfs\_shares/public

B. The command must NOT be executed on NFS client

C. The command must be executed on NFS server

**D. After execution of the command, /nfs\_shares/public will be synced with /var/nfs/nfs\_home**

**Question No:3**

**(Marks:1)**

**Vu-Topper RM**

In the context of X500, the DN refers to \_\_\_\_\_.

A. Defined Name

B. Designated Name

**C. Distinguished Name**

D. Destination Name

**Question No:4**

**(Marks:1)**

**Vu-Topper RM**

The NFS shared files are only available after executing the \_\_\_\_\_.

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نيك صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

- A. exportnfs
- B. sharenfs
- C. exportfs**
- D. sharefs

**Question No:5**

**(Marks:1)**

**Vu-Topper RM**

Which command can be used to change LDAP admin password.

- A. ldappasswd**
- B. ldapasswd
- C. ldappassword
- D. ldapps wd

**Question No:6**

**(Marks:1)**

**Vu-Topper RM**

The string "cn=admin,dc=vusna,dc=com" represents a \_\_\_\_\_.

- A. DN**
- B. RDN
- C. CN
- D. GN

**Question No:7**

**(Marks:1)**

**Vu-Topper RM**

To disallow directory traversal on NFS share, \_\_\_\_\_ is used.

- A. no-subtree-check
- B. subtree\_check
- C. no\_subtree\_check**
- D. subtree-check

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:8**

**(Marks:1)**

**Vu-Topper RM**

While integrating the LDAP on Ubuntu client, the nsswitch configuration requires at least \_\_\_\_\_ parameters to be changed to ldap.

- A. 4
- B. 3
- C. 1
- D. 2**

**Question No:9**

**(Marks:1)**

**Vu-Topper RM**

If client faces issues with LDAP authentication, which of the given services should be restarted after making any changes.

- A. krb5
- B. nscd**
- C. bind9
- D. ldap

**Question No:10**

**(Marks:1)**

**Vu-Topper RM**

Select the correct relevent configuration of /etc/pam.d/comon\_password for integrating LDAP based authentication.

- A. password [success=1 user\_unknown=ignore default=die]  
pam\_ldap.so try\_first\_pass
- B. password [success=1 user\_unknown=ignore default=die]  
use\_authok try\_first\_pass
- C. password [success=1 user\_unknown=ignore default=die]  
pam\_ldap.so use\_authok try\_first\_pass**
- D. password [success=1 user\_unknown=ignore default=die]  
pam\_ldap.so try\_second\_pass

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:11**

**(Marks:1)**

**Vu-Topper RM**

Which file shall be modified if you want to share the files with read-only permissions.

- A. /etc/shares
- B. /nfs/permissions
- C. /etc/exports**
- D. chmod <permission> <folder>

**Question No:12**

**(Marks:1)**

**Vu-Topper RM**

The common umask value used with pam\_mkhome for LDAP client configuration is \_\_\_\_\_.

- A. 077
- B. 070**
- C. 644
- D. 067

**Question No:13**

**(Marks:1)**

**Vu-Topper RM**

The directories to be shared through NFS are specified in \_\_\_\_\_.

- A. /usr/share
- B. /tmp/shares
- C. /var/exports
- D. /etc/exports**

**Question No:14**

**(Marks:1)**

**Vu-Topper RM**

By default, the configuration of DHCP services is stored on location \_\_\_\_\_ in linux server.

Reload Math Equations

- A. /dhcp
- B. /etc

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

- C. etc/dhcp/
- D. /etc/dhcp/

**Question No:15**

**(Marks:1)**

**Vu-Topper RM**

The \_\_\_\_\_ technique is used to find the FQDN associated with an IP address.

Reload Math Equations

- A. Forward DNS lookup
- B. Address lookup
- C. Reverse DNS Lookup**
- D. DNS lookup

**Question No:16**

**(Marks:1)**

**Vu-Topper RM**

In DHCP configuration, the host archmachine {} construct can be used to \_\_\_\_\_.

Reload Math Equations

- A. Assign dynamic address statically
- B. Assign ip address
- C. Allocate a fixed address corresponding to the physical address of machine**
- D. Filter the IP address assignment

**Question No:17**

**(Marks:1)**

**Vu-Topper RM**

The bind configuration file "named.conf.local" contains a parameters named "forwarders". What is the purpose of DNS forwarder?

- A. If DNS query cannot be resolved by the root DNS, it is sent to the forwarders.
- B. It tries to resolve DNS request before all others.
- C. If local DNS cannot resolve the DNS query, it is sent to the forwarders.**

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

D. If DNS entry is not found in local cache, it is sent to the forwarders.

**Question No:18**

**(Marks:1)**

**Vu-Topper RM**

The correct command used to install dhcp server on linux machine is

\_\_\_\_\_.

- A. sudo apt install dhcp
- B. sudo apt install -y isc-dhcp-server
- C. apt install dhcp-server
- D. sudo apt install dhcp-server**

**Question No:19**

**(Marks:1)**

**Vu-Topper RM**

With SSH, files \_\_\_\_\_.

- A. Can be exchanged with additional tool**
- B. Cannot be exchanged
- C. Can be exchanged with TFTP
- D. Can be exchanged

**Question No:20**

**(Marks:1)**

**Vu-Topper RM**

A digital certificate can be used for all of the given except

\_\_\_\_\_.

**Authentication**

**Question No:21**

**(Marks:1)**

**Vu-Topper RM**

Some certificates are going to expire and needs to be updated; which package will take care of the process?

- A. gnupg
- B. cURL
- C. ssh
- D. ca-certificates**

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:22**

**(Marks:1)**

**Vu-Topper RM**

Consider the path permissions, -RW-R--R--Select the correct statement about above path.

**A. The path is a file**

B. The path is a directory

C. The path is not visible to all users

D. The path has global writable permissions

**Question No:23**

**(Marks:1)**

**Vu-Topper RM**

Which digit in 0755 permission represents the ownership.

**A. 3rd**

B. There is no information about owner user

C. 1st

D. 2nd

**Question No:24**

**(Marks:1)**

**Vu-Topper RM**

The following command has been executed on linux server. cat /etc/passwd > list.txt Which of the given option is correct about the given command.

A. The contents of file list.txt will be replaced with the file passwd

B. The contents of file passwd will be appended to list.txt.

C. The passwd file will be moved to list.txt

**D. The file passwd will be copied to list.txt**

**Question No:25**

**(Marks:1)**

**Vu-Topper RM**

What will happen if the following command is executed in the terminal: echo "(./etc/os-release && echo "VERSION\_CODENAME")"

A. It will not write anything on the stdout

**B. It may print focal on some Linux servers**

C. The command will fail due to multiple quotes

بری صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

D. The command will fail due to multiple echo commands

**Question No:26**

**(Marks:1)**

**Vu-Topper RM**

To delete a non-empty directory following command can be used.

- A. `rm <DirectoryName>`
- B. `rmdir <DirectoryName>`
- C. `rm -r <DirectoryName>`**
- D. `rmdir -r <DirectoryName>`

**Question No:27**

**(Marks:1)**

**Vu-Topper RM**

The command "sudo ls -l" is executed in \_\_\_\_\_.

- A. User mode
- B. Standard mode
- C. Privileged mode**
- D. Root mode

**Question No:28**

**(Marks:1)**

**Vu-Topper RM**

gnupg is a \_\_\_\_\_ implementation of \_\_\_\_\_.

- A. IEEE's, RFC4880
- B. IETF's, OpenPGP
- C. GNU's, OpenPGP**
- D. ITU's, 802.11

**Question No:29**

**(Marks:1)**

**Vu-Topper RM**

Select the correct option which represents the world-writable permissions.

- A. 0777**
- B. 0000
- C. 0750

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نيك صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

D. 0555

**Question No:30**

**(Marks:1)**

**Vu-Topper RM**

Consider the following command: `sudo install -m 0755 -d /etc/apt/keyrings` Select a correct statement about the given command.

- A. It will make the etc, apt and keyrings directories world-executable
- B. It will make the keyrings directory world-readable**
- C. It will make the keyrings directory world-writeable
- D. The owner of the directory keyrings cannot write it

**Question No:31**

**(Marks:1)**

**Vu-Topper RM**

Consider the following command syntax: `useradd <username> <password>` Which is the correct option about the given command syntax.

- A. The syntax is incorrect as it must be prefixed with sudo
- B. The syntax is incorrect as useradd cannot specify password**
- C. The command is correct
- D. The command is correct if executed in privileged mode

**Question No:32**

**(Marks:1)**

**Vu-Topper RM**

OpenPGP is defined by \_\_\_\_\_ in \_\_\_\_\_.

- A. IETF, RFC4440
- B. IEEE, 802.16
- C. IETF, RFC4880**
- D. IEEE, 802.11

**Question No:33**

**(Marks:1)**

**Vu-Topper RM**

Consider the command given below: `curl -f -s -S -L <FILE_URL>`  
Select the correct statement for the given command.

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نيك صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

- A. It will fail due to redundant switches -s and -S.
- B. -L cannot represent a web URL
- C. -f should be replaced with -F
- D. -f will bypass the server errors**

**Question No:34**

**(Marks:1)**

**Vu-Topper RM**

Select a correct option which represents the world-readable permissions.

- A. 0777
- B. 0775
- C. 0555
- D. 0755**

**Question No:35**

**(Marks:1)**

**Vu-Topper RM**

The key used by a server for authenticating a client with password-less configuration of SSH is \_\_\_\_\_.

- A. Private Key of Server
- B. Private Key of Client**
- C. Public Key of Client
- D. Private Key of Client

**Question No:36**

**(Marks:1)**

**Vu-Topper RM**

The Latest stable version of Ubuntu Server available is \_\_\_\_\_.

- A. 26.04
- B. 20.04**
- C. 22.04
- D. 18.04

بري صحبت سے تھائی بہتر ہے اور تھائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:37**

**(Marks:1)**

**Vu-Topper RM**

How many passwords will be required to remotely login to 10 servers with SSH client using user1's private key.

- A. 10
- B. 2, One for Private key, Second for Remote user login
- C. 0
- D. 1**

**Question No:38**

**(Marks:1)**

**Vu-Topper RM**

SSH stands for \_\_\_\_\_.

- A. Secure Shell**
- B. Secure Server Hosting
- C. Secure System Host
- D. System Shell

**Question No:39**

**(Marks:1)**

**Vu-Topper RM**

The correct syntax to establish a SSH connection to a remote server using NAT is \_\_\_\_\_.

- A. ssh -p <REMOTE-PORT> <LOCAL-USERNAME>@<REMOTE-SERVER-IP>
- B. ssh -p <REMOTE-PORT> <REMOTE-USERNAME>@<REMOTE-SERVER-IP>**
- C. ssh <REMOTE-USERNAME>@<REMOTE-SERVER-IP>
- D. ssh -p <REMOTE-PORT> <REMOTE-USERNAME>@<LOCAL-IP>

**Question No:40**

**(Marks:1)**

**Vu-Topper RM**

The permission string "-RW-R--R--" has a decimal value of \_\_\_\_\_.

- A. 0311

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نيك صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

- B. 1055
- C. 0644**
- D. 0755

**Question No:41** (Marks:1) **Vu-Topper RM**

Select the correct command to determine the transmit queue Length on eth0 interface.

- A. ifstat eth0
- B. ifqueue eth0
- C. show interface eth0
- D. ifconfig eth0**

**Question No:42** (Marks:1) **Vu-Topper RM**

Consider you are in the home directory, what will be effect if you execute the following command.cd ../../

- A. You will be moved to the root directory**
- B. It is an Invalid command
- C. You will be moved to the hidden directory ../
- D. You will remain in the current directory

**Question No:43** (Marks:1) **Vu-Topper RM**

Linux OS treats devices as \_\_\_\_\_.

- A. Interfaces
- B. Folders
- C. Directories
- D. Files**

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:44**

**(Marks:1)**

**Vu-Topper RM**

When a client-server program is run in Linux system, the connection-end-points are created under the directory \_\_\_\_\_.

- A. /
- B. /end\_points
- C. /tmp**
- D. /run

**Question No:45**

**(Marks:1)**

**Vu-Topper RM**

The linux directory /lib contains \_\_\_\_\_.

- A. Dependencies of programs in /bin and /sbin**
- B. Dependencies of programs in /usr/bin
- C. Data for services
- D. Dependencies of programs in /etc

**Question No:46**

**(Marks:1)**

**Vu-Topper RM**

pwd command stands for \_\_\_\_\_.

- A. Print working directory**
- B. Current user password
- C. Password
- D. Path of working directory

**Question No:47**

**(Marks:1)**

**Vu-Topper RM**

"/dev/null" is an example of \_\_\_\_\_ in linux system.

- A. Default-device
- B. User-defined-device
- C. Pseudo-device**
- D. Physical-device

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نيك صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:48**

**(Marks:1)**

**Vu-Topper RM**

The Linux OS uses a \_\_\_\_\_ directory structure.

**A. Hierarchical**

B. Circular

C. Linear

D. Flat

**Question No:49**

**(Marks:1)**

**Vu-Topper RM**

myFolder/myLab/ex1.txt is an example of \_\_\_\_\_.

**A. Relative path**

B. Invalid path

C. Virtual path

D. Absolute path

**Question No:50**

**(Marks:1)**

**Vu-Topper RM**

What best describes the output of the following command. `dir *p.* > ~/d.txt`

A. Append the contents of working directory to the file d.txt.

B. List the file and folders with p at the end of their name.

**C. Redirect the output of the command `dir *p.*` to the file d.txt in home directory.**

D. Display the contents of the file located in the home path.

**Question No:51**

**(Marks:1)**

**Vu-Topper RM**

In Linux system, the devices without any physical hardware are known as \_\_\_\_\_.

A. Reserved Devices

**B. Pseudo Devices**

C. Soft Devices

D. Missing Devices

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:52**

**(Marks:1)**

**Vu-Topper RM**

The root/ path is a \_\_\_\_\_ in a linux system.

- A. Security risk
- B. Absolute Path**
- C. A home directory path
- D. Root Path

**Question No:53**

**(Marks:1)**

**Vu-Topper RM**

For a standard user, the command "./sbin/client" will \_\_\_\_\_ on Ubuntu system.

- A. Connect the client to server
- B. Report permission error
- C. Successfully run
- D. Not run**

**Question No:54**

**(Marks:1)**

**Vu-Topper RM**

Generally, shared directories can be enlisted using the command \_\_\_\_\_.

- A. dir shares
- B. ls /usr/shares
- C. ls**
- D. ls /mnt

**Question No:55**

**(Marks:1)**

**Vu-Topper RM**

The following command will \_\_\_\_\_. mkdir ~/d1 d2 d3

- A. Fail to execute
- B. Create directories d1, d2 and d3 in current working directory
- C. Create a directory d1 in home directory and directories d2 and d3 in current working directory**
- D. Create directories d1, d2 and d3 in the home directory

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:56**

**(Marks:1)**

**Vu-Topper RM**

The simplest way to delete an empty directory is \_\_\_\_\_.

- A. rmdir -r <DirectoryPath>
- B. rm <DirectoryPath>
- C. rmdir <DirectoryPath>**
- D. del <DirectoryPath>

**Question No:57**

**(Marks:1)**

**Vu-Topper RM**

A system administrator has found that a Ubuntu server has /selinux in its root path, What could be the reasons of the existence of above directory?

- A. OS may have security risk
- B. It is normal to have this directory
- C. Root path may have been corrupted.**
- D. It exists because of the first boot after the installation

**Question No:58**

**(Marks:1)**

**Vu-Topper RM**

In Linux file system, there could be \_\_\_\_\_ root(s).

- A. Zero
- B. Single
- C. Two
- D. Multiple**

**Question No:59**

**(Marks:1)**

**Vu-Topper RM**

By default, SSH connection is established on \_\_\_\_\_ port.

- A. Both Remote and local 22**
- B. Any
- C. Local 22
- D. Remote 22

بري صحبت سے تھائی بہتر ہے اور تھائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:60**

**(Marks:1)**

**Vu-Topper RM**

An active user part of SSH group has been deleted with userdel command, What would happen with remote connection.

- A. SSH connection will be terminated**
- B. SSH connection will remain active
- C. User connection will be put on hold
- D. User will not be deleted

**Question No:61**

**(Marks:1)**

**Vu-Topper RM**

The command "ssh -F /dev/null username@myserver.com" has been successfully executed on Linux server. What are the results of the command?

- A. SSH service will fail
- B. Active SSH connections will be terminated
- C. ~/.ssh/sshd\_conf will be bypassed**
- D. username@myserver.com will be logged in without password

**Question No:62**

**(Marks:1)**

**Vu-Topper RM**

\_\_\_\_\_ directory generally contains the common libraries on a Linux system.

- A. /sbin
- B. /bin
- C. /usr/lib
- D. /lib**

**Question No:63**

**(Marks:1)**

**Vu-Topper RM**

Which of the given statements is correct?

- A. By default root user exists on the system**
- B. sudo passwd is used to create root user

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

- C. sudo passwd -l root is used to create a root user
- D. sudo adduser root is used to create root user

**Question No:64** (Marks:1) **Vu-Topper RM**  
The .htaccess allows to customize the configuration of a webserver based on \_\_\_\_\_.

- A. conf. files
- B. content files
- C. conf. directories
- D. content directories**

**Question No:65** (Marks:1) **Vu-Topper RM**  
The .htaccess cannot be used to \_\_\_\_\_.

- A. Match URLs
- B. Filter URLs
- C. Change URLs**
- D. Redirect URLs

**Question No:66** (Marks:1) **Vu-Topper RM**  
Which of the given actions is performed by the command a2dissite?

- A. It re-associate a given site configuration
- B. It enables a given site configuration
- C. It disables a given site configuration**
- D. It de-associates a given site configuration

**Question No:67** (Marks:1) **Vu-Topper RM**  
The permissions of .htaccess file should be \_\_\_\_\_.

- A. 0777
- B. 0555

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

C. 0651  
**D. 0644**

**Question No:68** (Marks:1) **Vu-Topper RM**  
Select the correct statement about the difference between ServerRoot and DocumentRoot on Apache server.

- A. ServerRoot is OS root and DocumentRoot is user 's document's root
- B. ServerRoot hosts the webserver program files and DocumentRoot hosts the webserver contents**
- C. Both ServerRoot and DocumentRoot contains the Program files
- D. Both are same

**Question No:69** (Marks:1) **Vu-Topper RM**  
Which of the given options would be a reason if correct .htaccess files are not being processed on a webserver.

- A. "FollowSymLinks" is configured
- B. Indexes are not created
- C. "Order allow, deny" is incorrectly configured
- D. "AllowOverride All" is not configured**

**Question No:70** (Marks:1) **Vu-Topper RM**  
One of the valid uses of htaccess technique is to \_\_\_\_\_.

- A. Modify the content directories
- B. Redirect HTTPS to HTTP
- C. Redirect HTTP to HTTPS**
- D. Modify the requested content

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:71**

**(Marks:1)**

**Vu-Topper RM**

Consider the following rewrite rule and select the correct option.

RewriteRule ^(.\*)\$ http://%{HTTP\_HOST}%{REQUEST\_URI}  
[L,R=301]

A. It will redirect the non-HTTPS requests to Error 301

**B. There will be no more rules applied after this rule.**

C. It redirects the HTTPS to HTTP

D. It redirect the non-www requests to www requests

**Question No:72**

**(Marks:1)**

**Vu-Topper RM**

Common place of Apache configuration file is \_\_\_\_\_.

**A. /etc/apache2**

B. /usr/etc/apache2

C. /usr/bin/apache2

D. /var/etc/apache2

**Question No:73**

**(Marks:1)**

**Vu-Topper RM**

Consider the following rewrite code and select the correct URL that will be presented in the user browser.

URL : https://www.vu.com/course.php?code=1&sem=10

RewriteEngine On

RewriteRule ^([\^/\*]\*)([\^/\*]\*)\.php 1&sem=\$2 [L]

A. https://www.vu.com/1/10.php

B. https://www.vu.com/course.php?code=1&sem=10

**C. https://www.vu.com/10/1.php**

D. https://www.vu.com/course.php?code=10&sem=1

**Question No:74**

**(Marks:1)**

**Vu-Topper RM**

The correct syntax of the htpasswd usage to create a secure password is \_\_\_\_\_.

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نيك صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

- A. htpasswd -c ~/ u1.txt rashid
- B. htpasswd -c rashid ~/u1.txt
- C. htpasswd -c ~/u1.txt rashid**
- D. htpasswd -c rashid ~/u1.txt

**Question No:75**

**(Marks:1)**

**Vu-Topper RM**

Select the correct structure of virtual host configuration.

**A. <VirtualHost \*:80> DirectoryIndex index.html index.php  
ServerAdmin admin@myserver.com ServerName myserver.com  
ServerAlias www.myserver.com DocumentRoot  
/var/www/myserver</VirtualHost>**

B. <VirtualHost lo:\*> DirectoryIndex index.html index.php  
ServerAdmin admin@myserver.com ServerName myserver.com  
ServerAlias www.myserver.com DocumentRoot  
/var/www/myserver</VirtualHost>

C. <VirtualHost \*:80> DirectoryIndex index.html index.php  
ServerAdmin admin@myserver.com ServerName myserver.com  
ServerAlias www.myserver.com DocumentRoot  
/var/www/myserver<VirtualHost><VirtualHost \*:\*>

D. <VirtualHost \*:\*> DirectoryIndex index.html index.php  
ServerAdmin admin@myserver.com ServerName myserver.com  
ServerAlias www.myserver.com DocumentRoot  
/var/www/myserver</VirtualHost>

**Question No:76**

**(Marks:1)**

**Vu-Topper RM**

To match a certain request in .htaccess, the \_\_\_\_\_ keyword is used.

- A. FilterURL
- B. MatchURL
- C. RewriteCond**
- D. AclURL

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:77**

**(Marks:1)**

**Vu-Topper RM**

By default, the KDC uses \_\_\_\_\_ as database.

- A. LDAP
- B. mongoDB
- C. kdb**
- D. mysq

**Question No:78**

**(Marks:1)**

**Vu-Topper RM**

Select the correct statement about self-signed-certificates.

- A. Only external host on same network will trust the self-signed-certificates.
- B. Only external host will trust the self-signed-certificates.
- C. Self-signed-certificates are not trusted by any client and on any network.**
- D. All firefox clients trust the self-signed-certificates.

**Question No:79**

**(Marks:1)**

**Vu-Topper RM**

The DNS record SOA stores the \_\_\_\_\_.

- A. Transfer zone admin information
- B. Zone admin information**
- C. Bind server admin information
- D. Local admin Information

**Question No:80**

**(Marks:1)**

**Vu-Topper RM**

Select the correct statement about the difference between "A" and "AAAA" records.

- A. Type of addresses are same for both records.
- B. "AAAA" record can represent IP address but "A" record cannot.
- C. "A" record can represent IP address but "AAAA" record cannot.
- D. Type of addresses are different for both records.**

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نيك صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

**Question No:81**

**(Marks:1)**

**Vu-Topper RM**

The software package available in Linux for DNS is known as \_\_\_\_\_.

- A. bind**
- B. dns-server
- C. domain-server
- D. isc-dns-server

**Question No:82**

**(Marks:1)**

**Vu-Topper RM**

Kerberos can be part of \_\_\_\_\_ for enterprise-level organizations.

- A. LAMP solution
- B. IAM solution**
- C. LDAP solution
- D. LAM solution

**Question No:83**

**(Marks:1)**

**Vu-Topper RM**

The tickets generated by the KDC can be viewed with \_\_\_\_\_.

- A. kticket
- B. kls
- C. klist**
- D. showlist

**Question No:84**

**(Marks:1)**

**Vu-Topper RM**

Consider the following rewrite code and select the correct option.

```
SetEnvIf MM_COUNTRY_CODE ^(PK) PAKISTAN
```

```
RewriteCond %{ENV:PAKISTAN} ^1$
```

```
RewriteRule .* http://www.vusna.pk%{REQUEST_URI} [R=301,L]
```

- A. Visitors from Pakistan will be denied to access vusna.pk
- B. Visitors from Pakistan will be offered content from vusna.pk**

بري صحبت سے تنہائی بہتر ہے اور تنہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

- C. Visitors from Pakistan will be filtered
- D. The code is incorrect

**Question No:85** (Marks:1) **Vu-Topper RM**

For Kerberos service, Linux server requires to install \_\_\_\_\_.

- A. krb5-kdc and krb5-admin-server packages**
- B. krb5-kdc package
- C. kerberos-kernel-server package
- D. krb5-admin-server package

**Question No:86** (Marks:1) **Vu-Topper RM**

To enable authentication with KDC server \_\_\_\_\_.

- A. KDC must be installed on client machine
- B. No changes in configurations are required
- C. No additional packages are required
- D. Client machines configuration need to be changed**

**Question No:87** (Marks:1) **Vu-Topper RM**

The command "ldapadd" is used to \_\_\_\_\_.

- A. Add CN
- B. Add DC
- C. Add DN
- D. Add LDAP**

**Question No:88** (Marks:1) **Vu-Topper RM**

The DC refers to \_\_\_\_\_ in LDIF file.

- A. Designated Controller
- B. Department Component
- C. Domain Component**

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

## D. Database Component

**Question No:89**

**(Marks:1)**

**Vu-Topper RM**

After installing the ldap account manager package, it can be accessed on \_\_\_\_\_.

- A. https://<ldap\_server\_ipaddress>
- B. http://<ldap\_server\_ipaddress>
- C. http://<ldap\_server\_ipaddress>/iam
- D. http://<ldap\_server\_ipaddress>/lam**

**Question No:90**

**(Marks:1)**

**Vu-Topper RM**

After installing the Kerberos server, \_\_\_\_\_.

- A. Only the service should be restarted
- B. The .bashrc file must be reloaded
- C. The server machine must be rebooted**
- D. The root should relogin

**Question No:91**

**(Marks:1)**

**Vu-Topper RM**

On ldap client machines, the \_\_\_\_\_ package(s) are required.

- A. libnss-ldap, libpam-ldap, ldap-utils**
- B. libpam-ldap, ldap-utils
- C. ldap-utils
- D. libnss-ldap

**Question No:92**

**(Marks:1)**

**Vu-Topper RM**

The default admin account on LDAP account manager is \_\_\_\_\_.

- A. username=lam,password=lam
- B. username=iam,password=iam

بري صحبت سے تہائی بہتر ہے اور تہائی سے نیک صحبت بہتر ہے

**For More Help Contact What's app 03224021365**

- C. username=admin,password=admin  
**D. username=admin,password=lam**

**Question No:93** (Marks:1) **Vu-Topper RM**

In LDIF files, the ou stands for \_\_\_\_\_.

- A. Object Unit  
B. Omitted Unit  
**C. Organizational Unit**  
D. Output

**Question No:94** (Marks:1) **Vu-Topper RM**

The addprinc keyword is used in \_\_\_\_\_.

- A. kadmin.remote  
B. kadmin.local  
C. kadmin.root  
**D. kadmin**

**Visit My YouTube Channel**  
**For Subjective and More**  
**Important Files**  
**Channel Name = #VuTopperRM**

بري صحبت سے تتهائي بهتر ہے اور تتهائي سے نيك صحبت بهتر ہے

**For More Help Contact What's app 03224021365**